

电磁阀连接器 A 型带灯系列

Solenoid valve connectors type A-LED series

图例 / Figure & 订货号 / Order No.



ZT-A-AC-PG9-T
ZT-A-DC-PG9-T



ZT-A-AC-PG9-BR
ZT-A-DC-PG9-BR



ZT-A-AC-PG11-T
ZT-A-DC-PG11-T



ZT-A-AC-PG11-BR
ZT-A-DC-PG11-BR



ZT-A-AC-M18-T
ZT-A-DC-M18-T



ZT-A-AC-M18-BR
ZT-A-DC-M18-BR

图例 / Figure




AC 系列
AC Series






DC 系列
DC Series

电路图 / Circuit Diagram



尺寸图 / Drawing



产品描述 / Product Description & 技术参数 / Technical Data

类型 / Construction Type	A 型 / Type A
外壳颜色 / Housing Color	透明 Transparent / 茶色 Brown
外壳材料 / Housing Material	PC
接线座材料 / Internal Core Material	PA
接线端子数量 / Number Of Contacts	2+PE
螺纹 / Thread	内螺纹 / Internal thread
螺口 / Cable Gland	PG9/PG11/M18*1.5
LED 颜色 / LED Color	LED 红色 / LED red, 其他颜色可定制 / Other color is available on request
额定电压 / Rated Voltage	110V, 220V/12V, 24V
额定电流 (40°C) / Rated Current(40°C)	10A
锁紧方式 / Connector Locking System	中心螺钉 / Central screw
螺钉扭矩 / Contact Screw Torque	0.4N*m
机械寿命 / Mechanical Operation	≥ 50 次 / ≥ 50 mating cycles
防护等级 / Degree Of Protection	IP65
适用温度 / Operating Temperature	0°C -- +60°C (PVC); -40°C -- +125°C (NBR)
包装 / Packing	500pcs/ 箱, 其他包装可定制 / Other packing is available on request