

NEW

Tank accessories

SAW 115 series

Moisture control
desiccant breathers



PASSION TO PERFORM



FEATURES & BENEFITS

- ✓ Absorbs harmful water vapour
- ✓ Removes moisture in the headspace of equipment
- ✓ Eliminates rust-forming condensation
- ✓ Prevents sludge deposits and water-contaminated oil
- ✓ Filters damaging contaminants
- ✓ Prevents contamination ingress
- ✓ Delivers longer lubricant life
- ✓ Reduces wear and tear and extends the lifespan of machinery
- ✓ Comprehensive system protection

Second polyester filter element

Protects against migration of desiccant dust in the reservoir for maximum efficiency

Air Diffuser

Foam filter captures any oil mist and disperses incoming air evenly over filtration and drying areas.

Air Vents

Individual air intakes are opened based on flow requirements of the system. Plugs protect unit during shipping and storage.

Integrated Standpipe

Excellent vibration resistance, dissipates impact throughout the unit - eliminating weak points, and allows even airflow distribution



Protection from moisture and particulate contamination in lubricant and equipment

INTRODUCTION

To ensure greater efficiency and to maximise the lifespan of hydraulic and lubrication systems **the fluids should be kept free from solid and water contamination.**

However most fluid reservoirs must breathe to function, allowing water vapour and solid contaminants to enter. Temperature fluctuations in the reservoir will cause this water vapour to condense which will not only cause oxidation of the oil, but can also lead to considerable mechanical damage.

Standard air breathers remove some of the solid particles, but allow water vapour to pass freely.

WHAT IS A DESSICANT BREATHER?

The desiccant breather is a product that combines the filtration of pollution and absorption of free water contained in the air.

When the air enters the equipment through the breather, the filter layers remove the solid contamination while the desiccant agent holds the moisture.

While in service or during shut-down, the desiccant agent dries the equipment, absorbing moisture from the reservoir.

SAW is a range of desiccant breathers for hydraulic and lubrication systems.

WHAT CONTAMINATION PROBLEMS CAN DESSICANT BREATHERS PREVENT?


Liquid contamination is the cause of hydraulic and lubrication fluid performance issues.

Negative effects include:

- ✗ Increase of fluid acidity
- ✗ Reduction of lubrication performance
- ✗ Reduction of fluid longevity
- ✗ Creation of bacterial colonies
- ✗ Creation of ice at low temperatures

It also causes damage in the hydraulic systems:


- ✗ Creation of rust in the hydraulic tanks
- ✗ Wear and tear on equipment




SAW 115 GENERAL INFORMATION

Focus on

How does SAW Series works



SAW Series Benefits



Applications

Where is SAW series used?

MP Filtri's range of breathers are proven in a wide variety of applications, including: IBC tanks, Transformers, Storage Tanks in Hydraulics, Power Generation, Mining, Aviation, Storage, Manufacturing, and Petrochemical applications.

Where can't SAW series be used?

The SAW series is NOT suitable for the following environments:

- Systems with aggressive fluids (Phosphate esters, Hydrogen sulfide, Sulfuric acid, Highly alkaline cleaners)
- Systems with heavy duty cycles (Vibrations, Risk of impacts, Wide temperature range)
- Large systems

Hydraulic systems



Oil storage



Renewable energy



Gearbox



Transformers



Tanks



SAW 115 GENERAL INFORMATION

Description

Air Breathers

Max air flow up to 453 l/min (16 cfm)

SAW115 breather units can be added to systems or can replace existing breathers using the SMG 1 adapter.

As air is drawn into equipment through the breather, the layered filter elements remove particulate while the dessicant beads strip harmful moisture.

While in service or during shut-down, the dessicant beads attract moisture from inside the equipment reservoir, actively drying the system fluid.

Available features:

Male threaded connections 1" Multi-fit (NPT, BSPT, NPSM)

Common applications:

- Storage tanks
- Transformers
- Hydraulics power packs

AIR VENT HOLES

Important installation information

- The air vent holes are plugged for any new breather
- The plugs protect the dryer agent during storage and shipment
- The plugs must be taken out during the installation, according to the max hydraulic flow rate



Max hydraulic flow rate [l/min (cfm)]	Holes to open
up to 110 (4)	2
from 111 to 220 (4-8)	4
from 221 to 330 (8-12)	6
from 331 to 452 (12-16)	8

Technical data

Materials

Connection: Nylon
Internal Support Pipe: Nylon
Screen: Polycarbonate
Cover: Nylon
Dryer Agent: Silica Gel

Filter Efficiency

3µm absolute (B₃ ≥200)

Seals

NBR

Temperature

From -25 °C to +90 °C (from -20 °F to +200 °F)

Chemical Compatibility

Recommended:

- All Gear Oil
- Most Hydraulic Fluid
- Mineral and Synthetic Oil

Not Recommended:

- Phosphate Ester
- Hydrogen Sulphide
- Sulphuric Acid
- High Alkaline Cleaner

Humidity Protection

An MP Filtri standard breather is five times more effective than leading non-dessicant breathers.

Humidity Level

Below Ambient Conditions

SAW1153G03A00P01
protects 30,000+ cycles

Deliquescent:

Protects 5,000 cycles
(Testing parameters
23 °C, 30 l/min - 73 °F, 1 cfm)



Performances

		Max hydraulic flow @ 7 kPa (1 psi)	Water Absorption Capacity	Recommended max volume		Silica gel weight	Total weight
				Gearbox / Storage tank	Hydraulic reservoir		
Series	Length	[l/min (cfm)]	[ml (fl.oz)]	[l (gal)]		[kg (lb)]	
SAW115	1	453 (16)	118 (4)	757 (200)	227 (60)	0.32 (0.70)	0.60 (1.32)
SAW115	2	453 (16)	220 (7.45)	1325 (350)	379 (100)	0.56 (1.23)	0.90 (1.98)
SAW115	3	453 (16)	333 (11.3)	1893 (500)	757 (200)	0.84 (1.88)	1.20 (2.64)

SAW 115

Designation & Ordering code

COMPLETE BREATHER									
Series and size SAW115	Configuration example : SAW115 1 G 03 A 0 0 P01								
Length 1 2 3									
Connections to the tank G Thread 1"									
Filtration rating 03 Orange Silica Gel									
Seals A NBR									
Valve 0 Without valve									
Option 0 Standard									
Execution									
P01 MP Filtri standard									
Pxx Customized									

ACCESSORIES				
Series and size SMG Adapter Flange	Configuration example : SMG1 S A P02			
Connections to the tank S Without screws				
Seals A NBR				
Execution				
P02 MP Filtri standard				

Silica gel

Active breather



Depleted breather



Silica gel is the most efficient and economic moisture adsorbent for general applications.

A white breather means the unit has done its job keeping moisture out of your lubricants.

Whenever the colour changes from orange to white it's time to replace the breather with a new one.

All breathers should be changed at least once a year.


IMPORTANT

Dispose of the exhausted silica gel according to the regulations in force in the country of use.



SAW 115

Dimensions



All data, details and words contained in this publication are provided for information purposes only.
MP Filtri reserves the right to make modifications to the models and versions of the described products
at any time for both technical and / or commercial reasons.
The colors and the pictures of the products are purely indicative.
Any reproduction, partial or total, of this document is strictly forbidden.
All rights are strictly reserved.