


DIFFERENTIAL INDICATORS


Dimensions

DLA*71	
Electrical/Visual Differential Indicator	
Settings	Ordering code
1.2 bar ±10%	DL A 12 x A 71 P01
2.0 bar ±10%	DL A 20 x A 71 P01
5.0 bar ±10%	DL A 50 x A 71 P01
7.0 bar ±10%	DL A 70 x A 71 P01
9.5 bar ±10%	DL A 95 x A 71 P01




A/F 30
Max tightening torque: 65 N·m

Hydraulic symbol



Electrical symbol



Materials

- Body: Brass
- Base: Black Nylon
- Contacts: Silver
- Seal: HNBR - FPM


Technical data

- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC according to ISO 2943
- Degree protection: IP65 according to EN 60529
IP69K according to ISO 20653

Electrical data


- Electrical connection: IEC 61076-2-101 D (M12)
- Lamps: 24 Vdc
- Resistive load: 0.4 A / 24 Vdc

DLE*A50	
Electrical/Visual Differential Indicator	
Settings	Ordering code
1.2 bar ±10%	DL E 12 x A 50 P01
2.0 bar ±10%	DL E 20 x A 50 P01
5.0 bar ±10%	DL E 50 x A 50 P01
7.0 bar ±10%	DL E 70 x A 50 P01
9.5 bar ±10%	DL E 95 x A 50 P01




A/F 32
Max tightening torque: 95 N·m

Hydraulic symbol



Electrical symbol



Materials

- Body: Brass
- Base: Black Nylon
- Contacts: Silver
- Seal: HNBR - FPM


Technical data

- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC according to ISO 2943
- Degree protection: IP65 according to EN 60529

Electrical data


- Electrical connections: EN 175301-803
- Resistive load: 5 A / 250 Vac
- Available the connector with lamps

DLE*F50	
Electrical/Visual Differential Indicator	
Settings	Ordering code
1.2 bar ±10%	DL E 12 x F 50 P01
2.0 bar ±10%	DL E 20 x F 50 P01
5.0 bar ±10%	DL E 50 x F 50 P01
7.0 bar ±10%	DL E 70 x F 50 P01
9.5 bar ±10%	DL E 95 x F 50 P01




A/F 32
Max tightening torque: 95 N·m

Hydraulic symbol



Electrical symbol



Materials

- Body: Brass
- Base: Black Nylon
- Contacts: Silver
- Seal: HNBR - FPM

Technical data

- Max working pressure: 420 bar
- Proof pressure: 630 bar
- Burst pressure: 1260 bar
- Working temperature: From -25 °C to +110 °C
- Compatibility with fluids: Mineral oils, Synthetic fluids
HFA, HFB, HFC according to ISO 2943
- Degree protection: IP65 according to EN 60529

Electrical data

- Electrical connections: EN 175301-803
- Resistive load: 5 A / 250 Vac
- Thermal lockout setting: +30 °C

DIFFERENTIAL INDICATORS

Series	Configuration example 1:	DE	H	50	F	A	70	P01
DE Electrical or Electronic differential indicator	Configuration example 2:	DE	M	50	H	F	50	P01
DL Electrical / Visual differential indicator	Configuration example 3:	DE	S	25	H	A	10	P01
DT Electronic differential indicator	Configuration example 4:	DL	E	70	V	A	71	P01
DV Visual differential indicator	Configuration example 5:	DT	A	50	H	F	70	P01
	Configuration example 6:	DV	M	95	V			P01
	Configuration example 7:	DV	S	40	H			P01

Type DE - DL - DT	DE	DL	DT	Type DV
A Standard type	•	•	•	A With automatic reset
E For high power supply		•		M With manual reset
H Hazardous area	•			S Compact version
M With wired electrical connection	•			
S Compact version	•			

Pressure setting	DEA	DEH	DEM	DES	DLA	DLE	DTA	DVA	DVM	DVS
12 1.2 bar	•		•		•	•	•	•	•	
20 2.0 bar	•		•		•	•	•	•	•	
25 2.5 bar				•						•
40 4.0 bar				•						•
50 5.0 bar	•	•	•		•	•	•	•	•	
70 7.0 bar	•	•	•		•	•	•	•	•	
95 9.5 bar	•		•		•	•	•	•	•	

Seals	DEA	DEH	DEM	DES	DLA	DLE	DTA	DVA	DVM	DVS
F MFQ		•								
H HNBR	•		•	•	•	•	•	•	•	•
V FPM	•	•	•		•	•	•	•	•	•

Thermostat	DEA	DEH	DEM	DES	DLA	DLE	DTA
A Without		•	•	•	•	•	•
F With thermostat				•		•	•

Electrical connections	DEA	DEH	DEM	DES	DLA	DLE	DTA
10 Connection AMP Superseal series 1.5				•	•		
20 Connection AMP Timer Junior					•		
30 Connection Deutsch DT-04-2-P					•	•	
35 Connection Deutsch DT-04-3-P						•	
48 Connection M20			•				
49 Connection 1/2" NPT			•				
50 Connection EN 175301-803			•				•
51 Connection EN 175301-803, transparent base with lamps 24 Vdc							•
52 Connection EN 175301-803, transparent base with lamps 110 Vdc							•
70 Connection IEC 61076-2-101 D (M12)		•					•
71 Connection IEC 61076-2-101 D (M12), black base with lamps 24 Vdc						•	
80 Connection Stud #10-32 UNF				•			

Option
P01 MP Filtri standard
Pxx Customized

DESIGNATION & ORDERING CODE - DIFFERENTIAL INDICATOR PLUG

Series	Configuration example	T2	H
T2 Indicator plug			
Seals			
H HNBR			
V FPM			