








Product description			
Standard	EN175301-803	EN175301-803	
Construction type	A	A	
Description	P18 connector with screw terminals NBR profile gasket (PE) earth position H12	P18 connector with screw terminals NBR profile gasket (PE) earth position H12	
Housing colour	black	black	
Number of contacts	2+PE	2+PE	
Order no.	KA132000B9	KA132000B1	
Other options on request	grey housing	order no. KA132000A9	order no. KA132000A1
Cable gland	PG9	PG11	
Max. conductor size	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	
Drawing			
			
			
			
			
			
Technical data			
Pin dimension	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	
Rated voltage max.	250 V AC/DC	250 V AC/DC	
Rated current max. (EN 60512-5-2 test 5b)	10 A	10 A	
Contact resistance	15mΩ max.	15mΩ max.	
Overvoltage category	III	III	
Type of termination	screw M3	screw M3	
Contact screw torque	max. 0,5 N/m	max. 0,5 N/m	
Suitable cables	5 mm to 7 mm diameter	6 mm to 9 mm diameter	
Mounting	central screw M3x32,5	central screw M3x32,5	
Material			
Contact material	CuSn silver plated	CuSn silver plated	
Contact holder material	PA6 GF	PA6 GF	
Housing material	PA6 GF	PA6 GF	
Environmental conditions			
Protection class (EN 60529)	IP 65 when correctly assembled	IP 65 when correctly assembled	
Pollution severity (EN 60664-1)	3	3	
Temperature range	-40°C to + 100°C	-40°C to + 100°C	
	with silicon gasket	-40°C to + 125°C	
Inflammability class			
Contact holder	HB - UL 94	HB - UL 94	
Housing	HB - UL 94	HB - UL 94	
Packaging			
Packaging unit / Weight approx.	500 pieces / 14,5Kg	500 pieces / 14,5Kg	
Box dimensions	80 x 30 x 22 cm	80 x 30 x 22 cm	
Other accessory options			
to be ordered separately see pages 177-181	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	
	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	
	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	