Technical data

Filler / draining plugs

Aluminium drain plug

TKM is a range of aluminium compact plugs for draining of the fluid from the systems during the commissioning and maintenance procedures. They are directly fitted on the bottom of the tank.

The integrated magnet holds the ferrous contamination.

Available features:

- Male threaded connections up to G 1"

Common applications:

- Hydraulic systems
- Mobile machines
- Industrial equipment

Materials

- Body: Aluminium avec insert magnétique
- Seal: Inorganic fibre

Temperature

From -25 °C to +100 °C

Weight

TKMG13 14 g

TKMG16 23 g

TKMG20 42 g

TKMG26 95 g

TKMG33 98 g

Quantity


25 pcs/pack




Designation & Ordering code

	<u> </u>	COMPLETE DRAIN PLUG
Serie	s	Configuration example : TKM G20 B P01
TKM		
Conn	ections	
G13	G 1/4"	
G16	G 3/8"	
G20	G 1/2"	
G26	G 3/4"	
G33	G 1"	
Seals		
В	Inorganic fiber	
		Execution
		P01 MP Filtri standard
		Pxx Customized

84)-





Connections	ØD [mm]	A/F [mm]	ØE [mm]	H [mm]	H1 [mm]	H2 [mm]
G13	19	15	9.5	6	11.5	5.5
G16	22	18	8	9.5	13.5	7.5
G20	28	22	10	9.5	15.5	7.5
G26	35	27	12	10.5	20.5	8.5
G33	42	34	25	13	30.5	10.5