

External supply nominal voltage \pm 10%	Voltage code	Type of connector	Power consumption (2)	Code of spare coil DHE	
12 DC	12 DC	666 or 667	30 W	COE-12DC	
14 DC	14 DC			COE-14DC	
24 DC	24 DC			COE-24DC	
28 DC	28 DC			COE-28DC	
48 DC	48 DC			COE-48DC	
110 DC	110 DC			COE-110DC	
125 DC	125 DC		58 VA (3)	COE-125DC	
220 DC	220 DC			COE-220DC	
24/50 AC	24/50/60 AC			COE-24/50/60AC (1)	
48/50 AC	48/50/60 AC			COE-48/50/60AC (1)	
110/50 AC	110/50/60 AC			COE-110/50/60AC (1)	
230/50 AC	230/50/60 AC			COE-230/50/60AC (1)	
115/50 AC	115/60 AC			80 VA (3)	COE-115/60AC
230/50 AC	230/60 AC				COE-230/60AC
110/50 AC - 120/60 AC	110 RC	669	30 W	COE-110RC	
230/50 AC - 230/60 AC	230 RC			COE-230RC	

(1) Coil can be supplied also with 60 Hz of voltage frequency: in this case the performances are reduced by 10 \pm 15% and the power consumption is 52 VA.

(2) Average values based on tests performed at nominal hydraulic condition and ambient/coil temperature of 20°C.

(3) When solenoid is energized, the inrush current is approx 3 times the holding current.